



bringing the
world to you

Soli-MaX

Resilient






Soli Max Resilient




Key features

- Wide profile and flat footprint for increased stability and grip.
- Durable tread composition to ensure maximum service life.
- Finest quality 3-layer rubber compounds for proper rim fitment, comfort driving, and minimum wear resistance.
- High durability and loading capacity.
- Unique five-stage wearing tread design for extended usage time and greater traction.
- Continuous center lug for driver comfort with minimum vibration and reduced wear on the driveline.
- Large tread blocks and deep lugs to maximize life and traction.
- Unique tread design to ensure perfect grip and prevent skidding while lowering the heat buildup of the tyre.
- Low running cost and fuel consumption per kilometer.
- Warranty for 5yrs from production date or 2000hrs to 3000hrs product life which ever earlier.



Normal Mounting



Quick Mounting

SOLI MAX RESILIENT SOLID TYRE				
Category	Colours			
	Black	White	Grey	RAL Colours
Extra Premium	✓	✗	✗	✗
Premium	✓	✓	✓	✓
Standard	✓	✗	✗	✗

✓ Available ✗ Not Available





Extra Premium, Premium & Standard

3 Layer Construction

Tyre size	Rim size	Tyre Dimension (mm)		Load Capacity (kg)				
		Maximum overall width	Overall diameter (±2%)	Counterbalanced lift Trucks		Other vehicles (trailers)		
				Load wheel upto 16 km/h	Load steering wheel upto 25 km/h	Upto 6 km/h	Upto 10 km/h	Upto 25 km/h
4.00-8	3.00	104	410	950	730	950	860	730
15x4.5-8	3.00	115	378	1040	800	1040	945	800
5.00-8	3.00	120	453	1415	1090	1415	1285	1090
16x6-8	4.33	151	412	1270	975	1270	1150	975
18x7-8	4.33	154	455	2145	1650	2145	1945	1650
140/55-9	4.00	124	379	1170	900	1170	1060	900
6.00-9	4.00	141	524	1885	1450	1885	1710	1450
21x8-9	6.00	185	526	2755	2120	2755	2500	2120
200/50-10	6.50	191	458	2470	1900	2470	2240	1900
6.50-10	5.00	170	575	2340	1800	2340	2125	1800
23x9-10	6.50	196	588	3160	2430	3160	2865	2430
7.00-12	5.00	164	649	2920	2240	2920	2645	2240
23x10-12	8.00	218	584	3770	2900	3770	3420	2900
27x10-12	8.00	230	685	3900	3000	3900	3540	3000
7.00-15	5.50	179	727	3545	2725	3545	3215	2725
	6.00	179	727	-	-	-	-	-
28x9-15	6.50	216	691	-	-	-	-	-
	7.00	216	691	3445	2650	3455	3125	2650
250-15	7.00	223	723	4745	3650	4745	4310	3650
	7.50	223	723	-	-	-	-	-
28x12.5-15	9.75	286	691	5525	4250	5525	5015	4250
8.25-15	5.50	207	816	-	-	-	-	-
	6.50	207	816	4750	3650	4750	4300	3650
300.15	8.00	255	820	5850	4500	5850	5310	4500
355/65-15	9.75	300	822	7800	6000	7085	6430	5450
9.00-20	6.50	239	994	5400	4500	-	-	-
	7.00	239	994	5400	4500	-	-	-
	7.50	239	994	5400	4500	-	-	-
10.00-20	7.00	254	1037	6000	5000	-	-	-
	7.50	254	1037	6000	5000	-	-	-
	8.00	254	1037	6000	5000	-	-	-
11.00-20	7.00	255	1063	-	-	-	-	-
	7.50	255	1063	-	-	-	-	-
	8.00	255	1063	6540	5450	-	-	-
12.00-20	8.00	283	1096	7560	6300	-	-	-
	8.50	283	1096	7560	6300	-	-	-
	10.00	283	1096	7560	6300	-	-	-

The load-carrying capacity of drive wheels for CBF trucks applies to cyclic service only on a maximum distance of 10 km covered within 1 hour at a maximum speed of 25 km/h (Average speed lower than 10 km/h) and the maximum journey does not exceed 2,000 m. Cyclic service means applications where tyres are not used continuously at their Rated Load (LI) and their Reference Speed (SS).

Get in touch with us



www.amw-tyres.com



+94 76 093 1944

+94 77 753 6226



Material.handling@amwltd.com



www.amwltd.com

An  **Al-Futtaim** company