



bringing the
world to you

Eco-Trac

Resilient






Eco Trac Resilient




Key features

- Product life is 1000hrs with good driving habits.
- Suite for indoor, outdoor industrial application.
- Best performance in smooth or carpet road condition
- Average driving comfort.
- Good traction in dry and wet road condition.
- Application temperature 15-40 C
- Load Capacity and reference speed are according to the ETRTO std.
- Recommended Average driving speed < 10Km/h
- Low budget Tyres
- Warranty for 3yrs from production date or 1000hrs product life which ever earlier.



Normal Mounting



Quick Mounting



ECOTRAC RESILIENT SOLID TYRE				
Category	Colours			
	Black	White	Grey	RAL Colours
ECONOMY	✓	✗	✗	✗

✓ Available ✗ Not Available



Economy

2 Layer Construction

Tyre size	Rim size	Tyre Dimension (mm)		Load Capacity (kg)				
		Maximum overall width	Overall diameter (±2%)	Counterbalanced lift Trucks		Other vehicles (trailers)		
				Load steering Wheel up to 16km/h	Load steering Wheel up to 25km/h	Upto 6km/h	Upto 10km/h	Upto 25km/h
15x4.5-8	3.00	114	376	1040	800	1040	945	800
5.00-8	3.00	115	452	1415	1090	1415	1285	1090
16x6-8	4.33	147	410	1270	975	1270	1150	975
18x7-8	4.33	150	452	2145	1650	2145	1945	1650
140/55-9	4.00	124	379	1170	900	1170	1060	900
6.00-9	4.00	133	524	1885	1450	1885	1710	1450
21x8-9	6.00	182	522	2755	2120	2755	2500	2120
200/50-10	6.50	189	454	2470	1900	2470	2240	1900
6.50-10	5.00	150	575	2340	1800	2340	2125	1800
23xv9-10	6.50	192	580	3160	2430	3160	2865	2430
7.00-12	5.00	165	650	2920	2240	2920	2645	2240
7.00-15	5.50	175	718	3545	2725	3545	3215	2725
	6.00	175	718	-	-	-	-	-
28x9-15	6.50	209	681	-	-	-	-	-
	7.00	209	681	3445	2650	3445	3125	2650
250-15	7.00	215	709	4745	3650	4745	4310	3650
	7.50	215	709	-	-	-	-	-
8.25-15	5.50	201	803	-	-	-	-	-
	6.50	201	803	4750	3650	4750	4300	3650
300-15	8.00	247	806	5850	4500	5850	5310	4500

The load carrying capacity of drive wheels for CBF trucks applies to cyclic service only on a maximum distance of 10 km covered within 1 hour at a maximum speed of 25 km/h (Average speed lower than 10 km/h) and the maximum journey does not exceed 2,000 m. Cyclic service means applications where tyres are not used continuously at their Rated Load (LI) and their Reference Speed (SS).

Get in touch with us



www.amw-tyres.com



+94 76 093 1944

+94 77 753 6226



Material.handling@amwltd.com



www.amwltd.com

An  **Al-Futtaim** company