



bringing the
world to you

Soli-Trac

Resilient






Soli-Trac
Resilient


Soli Trac Resilient

Key features

- Extra deep tread with high lug depth for increased stability and driver comfort.
- Durable tread composition to ensure maximum service life.
- Finest quality 3-layer rubber compounds for proper rim fitment, comfort driving and minimum wear resistance.
- Good durability and loading capacity.
- Extra deep tread with high lug depth for extended usage time and greater traction.
- Large tread blocks and deep lugs to maximize life and decrease chipping and chunking.
- Unique tread design with angle treads that promotes even wear, prevents skidding and maintains low heat buildup.
- Low running cost and fuel consumption per kilometer.
- Warranty for 5yrs from production date or 1600hrs product life which ever earlier.



Normal Mounting



Quick Mounting



SOLITRAC RESILIENT SOLID TYRE				
Category	Colours			
	Black	White	Grey	RAL Colours
Standard	✓	✗	✓	✗

✓ Available ✗ Not Available

Soli-Tra [®] Resilient		Standard				2 Layer Construction		
Tyre size	Rim size	Tyre Dimension (mm)		Load Capacity (kg)				
		Maximum overall	Overall diameter	Counterbalanced lift Trucks		Other vehicles (trailers)		
				Load Wheel up to 16km/h	Load Steering Wheel up to 25km/h	Up to 6km/h	Up to 10km/h	Up to 25km/h
15x4.5-8	3.00	114	376	1040	800	1040	945	800
5.00-8	3.00	115	452	1415	1090	1415	1285	1090
16x6-8	4.33	147	410	1270	975	1270	1150	975
18x7-8	4.33	150	452	2145	1650	2145	1945	1650
140/55-9	4.00	124	379	1170	900	1170	1060	900
6.00-9	4.00	133	524	1885	1450	1885	1710	1450
21x8-9	6.00	182	522	2755	2120	2755	2500	2120
200/50-10	6.50	189	454	2470	1900	2470	2240	1900
6.50-10	5.00	150	575	2340	1800	2340	2125	1800
23x9-10	6.50	192	580	3160	2430	3160	2865	2430
7.00-12	5.00	165	650	2920	2240	2920	2645	2240
7.00-15	5.50	175	718	3545	2725	3545	3215	2725
	6.00	175	718	-	-	-	-	-
28x9-15	6.50	209	681	-	-	-	-	-
	7.00	209	681	3445	2650	3445	3125	2650
250-15	7.00	215	709	4745	3650	4745	4310	3650
	7.50	215	709	-	-	-	-	-
8.25-15	5.50	201	803	-	-	-	-	-
	6.50	201	803	4750	3650	4750	4300	3650
300-15	8.00	247	806	5850	4500	5850	5310	4500
9.00-20	6.50	235	985	5400	4500	-	-	-
	7.00	235	985	5400	4500	-	-	-
	7.50	235	985	5400	4500	-	-	-

The load-carrying capacity of drive wheels for CBF trucks applies to cyclic service only on a maximum distance of 10 km covered within 1 hour at a maximum speed of 25 km/h (Average speed lower than 10 km/h) and the maximum journey does not exceed 2,000 m. Cyclic service means applications where tyres are not used continuously at their Rated Load (LI) and their Reference Speed (SS).

Get in touch with us



www.amw-tyres.com



+94 76 093 1944

+94 77 753 6226



Material.handling@amwltd.com



www.amwltd.com

An  **Al-Futtaim** company